

## LED SUNSTRIP SHIFTER



## LEDBAR011

EK

- Red shift" coloi r shifting from amber to 3100K white
- Individual pixel control for stunning pixel-mapped effects
- Variety of dimming curves to accurately evoke the look and feel of this classic effect
- Selectable LED frequencies (from 600Hz ~ 25kHz) for flicker-free performance on camera
- DMX control, Master/Slave





## LED SUNSTRIP SHIFTER LEDBAR011

Photometrics	
Light Source	10W 3100K White + Amber LEDs
Beam Angle	16°
Field Angle	37°
Output	5658 lm / 1608 LUX @ 5 meters
Key Features	
Coloi r Output	Amber to Warm White
Pixel Matrix	10 x 1
Strobe	0-30 Hz
Dimming	4 dimming curve modes
Control	
Protocol	DMX
DMX Channels	3/5/6/8/9/21/27
Display	OLED function menu with 4 touch buttons
Power	
Mains	100V-240V 50/60 Hz
Consumption	151W

I/O	
Power connections	PowerCon In/Out
Data connections	XLR In/Out for DMX
Power Linking	Up to 16 units @230V / Up to 8 units @120V
Housing	
Material	Plastic and steel
Finish	Matte black
IP rating	IP20
Thermal	
Cooling	Convection
Physical	
Dimensions	1000 x 79 x 158 mm
Weight	6 KG
Dimensions	1000 x 75 x 231 mm
Weight	9.5 KG



SYDNEY MELBOURNE +61 2 9748 1122 +61 3 9681 7511 +61 7 3267 3177

BRISBANE

PERTH AUCKLAND +61892488119 +6498693293

