

SMART MODULA BASE

MUSMOD100

SMARTMODULA is a cable-free battery fixture which establishes a new form of decorative lighting for events, banquets and gardens.

FEATURES:

- MODULA design allows floor standing with flexible swivel joints, tilt-able stand or hanging with quick-lock omega brackets
- W-DMX
- The light emitters can slide on the track to allow perfect focus
- Fully interchangeable allowing for spot/wash or mixed configuration
- Options include:
 - (MUSMOD110)** 2x RGBW spot modules for SMARTMODULA, 10W, 15°
 - (MUSMOD115)** 6400K white wash module for SMARTMODULA, 25W, 60°
 - (MUSMOD111)** 2x 5600K white spot modules for SMARTMODULA, 3W, 15°



SMART MODULA BASE

LIGHT SOURCE

Source:	LED source as spot, wash or white
Source life expectancy:	>30.000 h

OPTICS

Beam Angle:	SPOT (Opt) 15°; WASH (Opt) 60°
-------------	--------------------------------

COLOUR SYSTEM

Colour mixing:	interchangeable light source
----------------	------------------------------

DYNAMIC EFFECTS

Auto Mode:	built-in programs with execution speed adjustment
Static colour mode:	Selection of static colour
Manual colour mode:	Manual adjustment of colour

BODY

Pan angle:	360° metal joint for 360° rotation of header bar
Tilt angle:	120° manual
Body:	Sturdy stretching aluminium body conceived for long-time durability
Body colour:	Matte black

CONTROL

Protocols:	W-DMX
Pixel control:	Pixel2pixel control
W-DMX:	Included, wireless solution receiver
Display:	black OLED touch display
W-DMX:	Included, wireless solution receiver
IR:	Infrared sensor controlled by remote

ELECTRONICS

Dimmer:	Linear 0~100% electronic dimmer
Strobe / shutter:	1-25 Hz, electronic
Operating temperature:	-10° ~ +45°
Flicker:	Flicker-free operation

ELECTRICAL

Power supply:	100-240V – 50/60Hz
---------------	--------------------

BATTERY:

Battery:	(Head) 1x14.8 V (Base - optional) 1x14.8V lithium
Recharge connection:	Power cable
Recharge time:	Head battery 5.5 h/max base battery 11h/max
Battery status:	LED battery status indicator
Battery life:	Up to 6 hours in full-on White

PHYSICAL

Cooling:	convection cooled
Suspension and fixing:	hanging bracket suitable for safe hanging and positioning
IP rating:	IP20
Dimensions (WxHxD):	466x(1694~2149)x1010mm
Weight:	w/o baseplate 23.5 kg, with baseplate 38.5kg
Power connection:	Neutrik powerCON IN connector



-RGBW 10W, 15°- MUSMOD110



-5600k 3W, 15°- MUSMOD111



Wash 6400k 25W, 60° - MUSMOD115



RGBW 25W, 60° - MUSMOD116

