

LED AuroCYC HEX IP

LEDCYC120

An innovative CYC unit well equipped for the harsh environments with an IP65 rating, this unit will take the bad weather head on with ease.

No matter what the application is, lighting a CYC or a façade outdoors the AuroCYC has you covered.

The 180W HEX colour LED engine provides the user a high CRI and extended colour range while the CCS3.0 calibration ensures every fixture reproduces the same output in mixed colour or CCT's between 1800K to 10,000K.



Optical System

Lamp Source	180W
Beam Angle	70°
Output	3545 Lux @ 5 Meters
CRI	> 93
CCT	1800K - 10000K

Electrical Specs

Voltage	100-240V AC, 50/60 Hz
Max Power	180W
Power Connection	Seetronic in and out
Signal Connection	5 pin in and out, Artnet

Control System

Dimmer	0-100% 16Bit
Cooling	Forced Convection
Control	DMX512, RDM
Display	On board Control, Dimming knob, 0-25Hz Strobe

Control modes BASIC(3CH)/SSP (SCH) /TOUR (13CH) /TR16 (20CH) / HSIC (7CH) / CMY (IOCH)

Appearance

Size	530x110x170mm
Weight	6kg
Casing	Flame-retardant plastic(V0)
Colour	Black

Work Environment

Ambient Temp	0-45°
IP Rated	IP65

Photometrics

