

# LED Fresnel RGBAL

## LEDFRE102

The LED Fresnel RGBAL is a 15°-50° manual zoom LED fixture with a powerful 100W LED engine comparable to 750W conventional fresnels. Featuring a CRI of 93, this fresnel boasts solid and dependable colour integrity. The LED Fresnel RGBAL uses the proprietary CCS colour consistency control technology that matches colour when used with other fixtures of the Silverstar range.



# Specifications

## Optical System

Lamp Source	100W (RGBAL)
Beam Angle	15° - 50°
CRI	93
CCT	1800K – 10000K

## Electrical Specs

Voltage	100 – 240VAC
Max Power	100W
Power Connection	TrueCon In/Out
Signal Connection	3 and 5 pin DMX In/Out

## Work Environment

Ambient Temperature	0°C - 45°C
IP Rated	IP20


## Control System

Dimmer	0 – 100%
Cooling	Forced Convection
Control	DMX512, RDM
Display	OLED display, on board control
Personality	HSIC/SSP/TOUR/TR16/CMY

## Appearance

Size	355x281x388.5mm
Weight	5.6kg
Casing	Die-cast aluminium
Colour	Black

## Photometrics



## Accessories

- LEDFRE101** Barndoor
- PSHDMX410** TrueCon/DMX Link Cable 1.5m
- PSHCAB403** TrueCon/DMX Link Cable 3m
- KUPRIG071** Mini Coupler with T-Handle Black
- KUPRIG110** Large Safety Wire 10kg SWL