



NEPTUNE 700 PROFILE IP65 MOVING HEAD

LEDMOV660

The NEPTUNE 700 Profile is a compact IP65-rated, 600W LED powerhouse with framing. The incredible 7°-50° zoom range creates a truly versatile fixture when used with the gobo wheel for stunning ariel effects or with one of the frost filters to deliver a soft edge, wide coverage wash. The animation wheel provides captivating effects such as fire or waterwave simulations, adding more dynamic visual effects to your show. The fixture features a high-efficient optic system that delivers excellent performance. It also incorporates a linear CMY colour system, providing a wide range of colours and seamless color mixing capabilities. This enables the fixture to produce vibrant and rich colours for stunning lighting effects.

NEPTUNE 700 PROFILE IP65 MOVING HEAD

Optical System

Light Source	600W White LED module
Beam Angle	7°-50°
Electric Specs	
Voltage	100-240V AC, 50/60 Hz
Max Power	750W
Driver Current	3.8A
Power Connection	Seetronic PowerKon (TRUE1 Compatible)
Data connection	3 + 5 Pin XLR, RJ45 (Art-Net)
Control System	
Pan/tilt rotation	540°/270° (8-16bit)
Dimmer	0-100% 16Bit
Cooling	Direct Convection
Control methods	DMX512, RDM, ARTNET, SACN, W-DMX
Display	OLED with onboard menu
Dimming	0-100% 16Bit
Con Personality	BASIC/35CHS, STANDARD/41CHS, Extend/44CHS
Special	Pan/Tilt movement blackout, user-selectable pan/tilt ranges, gravitation sensor for auto screen positioning

Appearance

Size	416x358x729mm
Weight	36kg
Casing	Flame-retardant plastic(V0)
Colour	Black


Effect system

,	
Rotating gobo	7 Gobos + White,Gobo-flow effect, Gobo shake, Bi-directional rotation
Static gobo	10 + 1 Gobos
Framing system	4 shutter blade; Each blade's angel and direction can be individual controlled, fully blackout; The whole Framing module is ±60°.
Colours:	One colour wheel (6 dichroic-filters +White, Rainbow-flow effect)
Prism:	One piece of 4 F prism with bidirectional rotation, Speed adjustable
CMYK	СМҮ,СТО
Focus:	Motorized linear focus
Frost:	light+medium 2 Frost filter

Work Environment

Ambient Temp	0-45°
IP Rated	IP65

Photometrics



Rotating Gobos













Fixed Gobos

































