





00000

Ultra-slim high-power RGB LED panel with 3 independently controllable sections







## LITEPANELT18

## Lightweight, versatile RGB LED panel with 3-section control, featuring:

- 18 x 3W RGB LED panel with integrated barndoors
- High-frequency LED modulation for flicker-free video playback
- Built-in sound-active and auto (stand-alone) programs
- Colour macros and selectable colour temperature presets
- Four selectable dimming curves
- Manual colour mixing via onboard menu
- Power In and Out connections for linking multiple units
- Infrared sensor for optional IR6 remote control
- USB port for optional UFI wi-fi transceiver for wireless DMX control



MELBOURNE

+61 3 9681 7511

BRISBANE

+61 7 3267 3177

www.showtech.com.au

## Specifications

Product	Lite-Panel T18		
Code	LEDNIT160		
Lamp Source	18 x 3W Tri-colour LED (RGB)		
Power Supply	100-240V AC, 50/60Hz		
Power Consumption	40W		
DMX Connection	3-pin XLR In/Out		
DMX Channels	3/5/9/13		
Beam Angle	16° (discrete) 32° (array)		
Output	470 lux @ 5m		
Dimensions	395(L) x 44(W) x 260(H)mm		
Weight	4.5 kg		

Channel Allocation					
	3-CH	5-CH	9-CH	13-CH	
1	Red	Dimmer	Dimmer	Red 1	
2	Green	Red	Red	Green 1	
3	Blue	Green	Green	Blue 1	
4		Blue	Blue	Red 2	
5		Shutter	Shutter	Green 2	
6			Colour Presets	Blue 2	
7			Auto Programs	Red 3	
8			Auto Speed	Green 3	
9			Dimmer Curve	Blue 3	
10				Auto Programs	
11				Auto Speed	
12				Dimmer	
13				Shutter	

PERTH

+61 8 9248 8119



AUCKLAND +64 9 869 3293

