

# LED Profile VW500

## LEDPRO135

The LED Profile VW500 features an exceptionally powerful 500W RGBAL LED engine, allowing for considerable brightness, surpassing older 1000W conventional fixtures. It features complete independent control of all discrete colour sources, and a preset colour temperature range of 2800K to 8000K. Boasting a high CRI of 95 and quiet operation through selectable fan modes, it is suitable for all live and studio applications.



## **Specifications**

#### **Optical System**

| Lamp Source | 500W (RGBAL)  |
|-------------|---------------|
| Output      | 11622lm       |
| CRI         | 95            |
| CCT         | 2800K – 8000K |

#### **Electrical Specs**

| Voltage           | 100 – 240VAC, 50/60Hz |
|-------------------|-----------------------|
| Consumption       | 330W Continuous       |
| Power Connection  | PowerCon In/Out       |
| Signal Connection | 5 pin XLR In/Out      |

#### **Appearance**

| Size   | 596x288x545mm      |
|--------|--------------------|
| Weight | 8kg                |
| Casing | Die-cast aluminium |
| Colour | Black              |

#### **Work Environment**

| Ambient Temperature | -10°C - 45°C |
|---------------------|--------------|
| IP Rating           | IP20         |

#### **Control System**

| Dimmer      | 0 – 100% Linear with 4 curves                |
|-------------|--|
| Cooling     | Forced Convection                            |
| Control     | DMX512, RDM                                  |
| Display     | TFT display, on board control                |
| Personality | 1Ch/4Ch/5Ch/7Ch/11Ch/13Ch/<br>13Ch2/17Ch/HSV |


#### **Accessories**

| LEDPRO150        | Diffuser Filter                            |
|------------------|--|
| LEDPRO152        | Gobo Holder                                |
| LEDPRO154        | Iris                                       |
| Lenses available | 14°/19°/26°/36°/50°<br>15° - 30°/25° - 50° |

### **Photometrics**

Distance (m)


Beam Angle: 19°



Distance (m) Luminance (lux)

Beam Angle: 26° Full o 1m 3m 5m 7m 10m 77310 8590 3092 1577 773

Beam Angle: 36°



Full o Distance (m)

Beam Angle: 50° 1m 3m 5m 7m 10m 18720 2080 748 382 187



Luminance (lux)

