









RGBW IP65-rated wash light with snap-on beam shaping filters and advanced thermal (fanless) design

With W-DMX receiver onboard









LED Fusion Wash Q XLVIII

LEDWSH480

OUTDOOR RATED RGBW WASH


- 48 x 10W RGBW LEDs deliver 22K lumens of perfectly blended colour
- Interchangeable beam shaping filters for precise control of light output
- 3 zone independent control of horizontal sections
- Silent operation suitable for indoor studio as well as outdoor use
- Selectable LED modulation for flicker-free output from 600Hz ~ 25kHz
- Ultra-linear dimming technology for flawless colour mixing
- Indestructible diecast body and tempered glass front panel
- Virtual color wheel and white presets from 1800K~8000K
- Four selectable dimmer curve modes
- Quick-Lock (Omega) bracket for easy installation
- Available optics: 8°, 15°, 25°, 45°
- Included accessories: 60° Diffuser, Omega bracket, saftey cable for diffuser
- Optional accessories: Barndoors, diffusers 20°/30°/50°/60°/60x10°/60x30° frost
- RDM, DMX and W-DMX wireless control

Photometrics

48 x 10W RGBW LEDs
25°
22760 lm
5364 lux @ 5 meters @ 25°
+/- 90° (manual)
RGBW
1-30 Hz
4 dimming curve modes
RDM, DMX and W-DMX
4 / 6 / 10 / 12
OLED display with touch navigation menu
100 - 240 VAC, 50/60 Hz
521W







Power connections	Seetronic PowerKon IP65 In/Out
Data connections	5 Pin IP65 XLR In/Out
Power linking	up to 4 units @ 230V
Housing	
Material	Diecast aluminum, tempered glass
Finish	Matte black
IP rating	IP65
Thermal	
Cooling	Passive (fanless)
Max. Ambient	40°C
Min. Ambient	-10°C
Physical	
Dimensions	563 x 93 x 314 mm
Weight	12.9 KG



SYDNEY MELBOURNE +61297481122 +61396817511

BRISBANE +61 7 3267 3177 PERTH A +61892488119 +

AUCKLAND +6498693293

