



Exterior Wash 210

Exterior™ Wash 210 is a powerful, compact and energy-efficient LED lighting fixture designed to illuminate mid-sized structures and building facades. A discreet, optional snoot integrates seamlessly with the slick design of the fixtures. It has built-in display for ease-of-use, a wide selection of beam angles and is fully IP-rated for permanent outdoor use.

The Exterior Wash 210 is designed for superior color mixing applications and is based on quad-color premixed LEDs.

Uniform color mixing with 6 beam angle options

Functional and discreet optional snoot which integrates with the design of the fixtures

Control via DMX, RDM and OLED display

GALLERY



FEATURES

- Powerful premixed LEDs
- Up to 4900 lumens at full white (RGBW)
- Six different beam angle options
- Internal power and control (DMX, RDM and OLED display)
- Rugged IP66 housing
- 0–100% intensity control

TECHNICAL SPECIFICATIONS

Physical

Length: 270 mm (10.7 in.)
Width: 334 mm (13.2 in.)
Height: 382 mm (15.1 in.)
Weight: 13.0 kg (28.7 lbs.)

Dynamic Effects

Intensity: 0 - 100%
Color mixing: RGBW

Control and Programming

Control systems: DMX, RDM
DMX channels: 4
Setting, addressing, standalone programming: Control panel with OLED display
Receiver: RS-485
Firmware update: Serial upload via DMX link
DMX compliance: USITT DMX512-A
RDM compliance: ANSI/ESTA E1.20

Optics

Minimum LED lifetime: 50 000 hours (to >70% luminous output) *
Light source: RGBW quad-color LED
Beam angle options: 10°, 14°, 22°, 41°, 61°, 14° x 61°

*Figure obtained under manufacturer's test conditions:

Photometric Data

Total luminous output: 4500 lumens

Construction

Protection rating: IP66
Color: Clear anodized (standard), black or white (optional)
Housing: Cast aluminum
Effective Projected Area (EPA): 0.1 m² including snoot
Impact resistance: IK08 (with control panel display cover plate installed)
Corrosion resistance: C5-M (very high corrosivity / marine, ISO 12944)
RoHS compliant

Installation

Orientation: Any

Mounting: Adjustable yoke

Vertical aiming: TBA

Minimum distance to illuminated surfaces: 0.2 m (0.6 ft.)

Connections

Power connection: 1.8 m (5.9 ft.) cable tail without connector

Data connection: 1.8 m (5.9 ft.) open ended 5-conductor combined input + output cable tail

All cable entries: IP68 cable gland

Electrical

AC power: 100 - 240 / 277 V nominal, 50/60 Hz

Power supply unit: Integrated, auto-sensing multi-voltage

Power consumption, steady state, all LEDs at zero intensity: 3 W

Typical Power and Current

120 V, 60 Hz: 1.4 A, 170 W, PF 0.99

230 V, 50 Hz: 0.8 A, 170 W, PF 0.95

Measurements made at nominal voltage. Allow for a deviation of +/- 10%:

Thermal

Cooling: Convection

Maximum ambient temperature (Ta max.): 45° C (113° F)

Minimum ambient temperature (Ta min.): -30° C (-22° F), power must be maintained below 0° C (32° F)

Maximum surface temperature, steady state, at 40° C ambient: 55° C (131° F)

Total heat dissipation (calculated, +/- 10%): 485 BTU/hr

Approvals

EU safety: EN60598-2-5 (EN60598-1), EN62471, EN62493, EN60598-2-1

EU EMC: EN55015, EN61547, EN61000-3-2, EN6100-3-3, EN61000-4-2, EN6100-4-4, EN6100-4-5

US safety: ANSI/UL 1598

US EMC: 47 CFR Part 15 Class A

Canadian safety: CSA C.22.2 No. 250

Australia/NZ: C-TICK N4241 / RCM

Included Items

Power cable: Cable tail, 1.8 m (5.9 ft.), external diameter 9.5 mm (0.38 in.), installed

Data cable: Cable tail, 1.8 m (5.9 ft.), external diameter 6.5 mm (0.26 in.), installed

Accessories

Optical:

Exterior Wash 200 Series, narrow diffuser kit: P/N 91610154

Exterior Wash 200 Series, medium diffuser kit: P/N 91610153

Exterior Wash 200 Series, wide diffuser kit: P/N 91610152

Exterior Wash 200 Series, very wide diffuser kit: P/N 91610151

Exterior Wash 200 Series, asymmetric diffuser kit: P/N 91610150

Exterior Wash 200 Series, glare shield / snoot: P/N 91611745

Related Items

Martin USB interface box incl. cables: P/N 90758090

M-PC 2U™ incl. Martin M-DMX Interface Box and USB cable: P/N 90737070

Ordering Information

Exterior Wash 210, 10°, EU, aluminum: P/N 90509088

Exterior Wash 210, 10°, US, aluminum: P/N 90509095




A C C E S S O R I E S




EW 200
ASSYMETRICAL
DIF KIT/BEZEL
P/N: 91610150




EW 200 MEDIUM
DIF KIT/BEZEL
P/N: 91610153



EW 200 NARROW
DIF KIT/BEZEL
P/N: 91610154



EW 200 VERY
WIDE DIF
KIT/BEZEL
P/N: 91610151



EW 200 WIDE DIF	EXTERIOR WASH
KIT/BEZEL	200 SNOOT
P/N: 91610152	P/N: 91611745