

# DOTQ set of 6 with case

## MUSDOT101

DOTQ is an ultra-compact, wireless, battery LED accent luminaire designed to light up the entirety of the inside or outside of a room. The compact form factor and chrome finish allows it to be used anywhere that needs a 'little lift' to finish off the perfect event design.

### FEATURES:

- 1x15 RGBW LEDs
- 15° to 23° zoom range
- Adjustable foot support for tilt regulation (up to 20°)
- IP65 rated
- DOTQ-PACK including ABS flight case containing 6 fixtures, charging station, top hats, magnetic frost filters, IR controller, eye bolts, suction cups and yokes
- Up to 6 hours battery in full on white.



# DOTQ Set of 6 with case

## MUSDOT101

### LIGHT SOURCE

Source:	1x15W RGBW LED
White Presets:	2800-9000K
Lux:	710lux @3m full
Source life expectancy:	>50.000 h

### OPTICS

Beam Angle:	15°
Field Angle:	23°
Additional optics:	Magnetic Frost filter inc for wider diffusion

### COLOUR SYSTEM

Colour mixing:	RGBW/FC
White presets:	2800-9000K
Colour wheel:	Virtual colour wheel with presets
Macros:	built-in white presets

### DYNAMIC EFFECTS

Auto Mode:	built-in programs with execution speed adjustment
Static colour mode:	Selection of static colour
Manual colour mode:	Manual adjustment of colour

### BODY

Tilt angle:	° adjustable foot support (up to 20°)
Body:	sturdy polycarbonate body
Body colour:	Mirror finishing

### CONTROL

Protocols:	W-DMX, RDM
DMX channels:	5 / 9 channel
Display:	3-Chars display
W-DMX:	Included, wireless solution receiver
RDM:	RDM ready for fixture remote monitor and settings

### ELECTRONICS

Dimmer:	Linear 0~100% electronic dimmer
Strobe / shutter:	1-25 Hz, electronic
Operating temperature:	-10° ~ +45°
Flicker:	Flicker-free operation

### ELECTRICAL

Power supply:	100-240V – 50/60Hz
---------------	--------------------

### BATTERY:

Battery:	11,1V lithium
----------	---------------

Battery life in colour change mode up to: 10 hours

Estimated battery life in single mode : 15 hours

Estimated battery life in full-mode: 5 hours

Recharge connection: Power cable

Recharge time: 3h/max

Battery status: LED battery status indicator

### PHYSICAL

Cooling: convection cooled

Suspension and fixing: hanging bracket suitable for safe hanging and positioning

IP rating: For temporary outdoor use - IP65 (front) - IP54 (bottom)

Dimensions (WxHxD): 88x88x63mm

Weight: 0.6 kg

