

Mosaico FX100

Image projector with dual animation wheel and 1 gobo/color slot, 100W LED source



Mosaico FX100 is an 100W white source LED IP66 image projector, engineered to be the modular platform to add building blocks to design your creative architectural lighting landscape.

Mosaico FX100 is supplied with two controllable effect wheels on board made in structured glass material to animate your projection, with linear motion control for creating reflected water, blowing fire or northern lights effects. The kit contains also one indeaxable gobo holder and a colour holder both with magnetic attachment.

Mosaico FX100 is compatible with a wide range of high definition optics, each optimized for the required application (animation or image projection): 15°, 30°, 50° and 70°.

This unit can be controlled via DMX, both wired and wireless and also easily operated locally through the simplified stand alone operations.

Please note that **Mosaico FX100** do not ship with a lens or other images or colors. Choose from the available lenses when ordering to meet your design requirements.

MAIN FEATURES

- 100W White LED Source Image and Effect light projector
- 15°, 30°, 50° and 70° available optics (not included), Image or Effects optimized
- DMX, CRMX Wireless and local stand alone control

VERSIONS

Code	Housing
MOSAICOFX100GY	Gray
MOSAICOFX100BK	Black

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source:100 W high-power white LED
- CCT:8'000K
- Luminous flux:(15°) 3'174 lm; (30° - WT) 3'246 lm; (30° - GB) 3'029 lm; (50° - WT) 3'646 lm; (50° GB) 2'217 lm; (70°) 2'367 @full
- Lux:(15°) 1'612 lx; (30° - WT) 954 lx; (30° - GB) 114 lx; (50° - WT) 345 lx; (50° GB) 179 lx; (70°) 176 lx @5 m full
- Source life expectancy: > 30.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

- Optics:interchangeable - see available accessories
- Focus: manual

COLOUR SYSTEM

- Colour wheel: available as accessory MFX100CW
- Other: included 1 static holder with magnetic positioning

DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer
- Gobo size (BW):outer: 26,9 mm - image: 22 mm
- Gobo size (Color):outer: 26,9 mm - image: 20,5 mm
- Fixed gobos: Fix gobo wheel available as accessory MFX100GW
- Static mode: selection of static dimmer and effects rotation mode
- Other: included 1 static gobo holder with manual indexing gear and magnetic assembly
- Other: 2 rotating wheels with magnetic mounting (structured glass included, color/gobo/animation and other wheels available as optional accessories)

BODY

- Body: weatherproof IP66 construction
- Body colour: RAL 9006 or RAL 9004
- Other:Inspectable cover window for effects and gobo replacement and maintenance

CONTROL

- Protocols: DMX512, RDM, CRMX + WDMX, 3 push encoder
- Stand Alone:3 push encoder
- DMX channels:8 channel
- Wireless Control: included, LumenRadio Timo Fx DMX/RDM compatible with both CRMX (Lumen Radio) and W-DMX (Wireless DMX)

- RDM: RDM for remote monitoring and settings
- Display: user interface through DATAMASTER external coder (not included)
- Firmware upgrade: yes, via USB - DMX interface (UPBOXPRO/UPBOX2) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100%, electronic and manual knob dimmer
- Dimmer curves: selectable dimming modes available
- Strobe / shutter:1-30 Hz, electronic
- Operating temperature: -20° C / +45° C (-4° F / +113° F)
- LED Control: flicker free frequency with adjustable PWM
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption:127 W
- Standby power:7W
- Output (at 230V):15 units on a single power line
- Power factor:>0.95
- Inrush current:<30A @115VAC /<50A @230VAC

PHYSICAL

- IP rating:66 for outdoor installations
- IK rating:09
- Cooling: active, silent operation
- Suspension and fixing: bracket for hanging and positioning
- Adaptors: XLR and BARE END 16A adaptors included
- Signal connection:35 cm moulded IP signal IN/OUT connectors
- Power connection:35 cm moulded IP power IN/OUT connectors
- Dimensions (WxHxD):224x261x221 mm
- Weight:5,7 kg

CERTIFICATIONS / APPROVALS


- Certifications / Approvals: CE, UKCA, RCM

ACCESSORIES & RELATED PRODUCTS


▪ MFX100BAG1U	Pelican case for 1 pc of MOSAICOFX100	▪ MFX100GW	Gobo wheel for MOSAICOFX100 serie (gobos not included)
▪ MFX100WBRAKGY/BK	Wall bracket for MOSAICOFX100, grey/black housing	▪ MFX100CW	Color wheel for MOSAICOFX100 serie
▪ MFX100FBRAKGY/BK	Floor bracket for MOSAICOFX100, grey/black housing	▪ MFX100GH	Gobo holder for MOSAICOFX100 serie (gobo not included) with manual indexing
▪ MOSUNIBRACKJR	Bracket for MOSAICOJR for wall mounting and suspension on poles	▪ MFX100CH	Color holder for MOSAICOFX100 serie (color not included)
▪ MFX100LWGN	15° lens for MOSAICOFX100 series, narrow for water effect and gobo	▪ MFX100SNOOT BK/GY	Snoot for MOSAICOFX100 series grey/black colour
▪ MFX100LWGVV	70° lens for MOSAICOFX100 series, very wide for water effect and gobo	▪ MFX100SNOOTPROT BK/GY	Anti tampering full snoot with front glass grey/black colour
▪ MFX100LWTM	30° lens for MOSAICOFX100 series, medium for water effect	▪ AWEXAC12ADP	Power adapter from AWEXAC1 cable series to AWEXAC2 cable series
▪ MFX100LWTW	50° lens for MOSAICOFX100 series, wide for water effect	▪ AWEXDC1221ADP	Signal adapter kit from AWEXDC1 series to AWEXDC2 series and vice versa
▪ MFX100LGBM	30° lens for MOSAICOFX100 series, medium for gobo	▪ AWEXAC1L03/05/10/20	IP67 power extension cable for outdoor architectural projectors, L.03/05/10/20 m
▪ MFX100LGBW	50° lens for MOSAICOFX100 series, wide for gobo	▪ AWEXDC1L03/05/10/20	IP67 DMX extension cable for outdoor architectural projectors, L.03/05/10/20 m
▪ GBVFX100120F06	Cyan filter with white stripes for MOSAICOFX100	▪ UPBOX1UP5	Firmware uploader kit, USB IN, 5pin XLR DMX OUT, USB OUT
▪ GBVFX100220F03	Red filter with white stripes for MOSAICOFX100	▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
▪ GBVFX100320F04	Green filter with white stripes for MOSAICOFX100	▪ RSR1235B	Steel security cable for hanging bodies, inox steel shackle, L=120 cm, black
▪ MFX100RAINW	Structured glass RAIN effect animation wheel	▪ LRLUNA	Single Universe DMX transceiver with Bluetooth
▪ MFX100HAMMERHEADW	Structured glass HAMMERHEAD effect animation wheel	▪ LRAURORA	Single Universe DMX/RDM transceiver with WiFi and Bluetooth
▪ MFX100D35C	Color for MFX100CH for MOSAICOFX100, 34,5 mm d. (RED, GREEN, BLUE, CYAN, MAGENTA, YELLOW, PINK MARINE, LIGHT ORANGE, LIGHT GREEN)	▪ MFX100AW	Animation wheel for MOSAICOFX100 serie
▪ MFX100D35CH	Half Color for MFX100CH for MOSAICOFX100, 34,5 mm d. (RED, GREEN, BLUE, CYAN, MAGENTA, YELLOW, PINK MARINE, LIGHT ORANGE, LIGHT GREEN)		
▪ MFX100WE1	Water effect wheel for MOSAICOFX100 series, short axis 1		
▪ MFX100WE2	Water effect wheel for MOSAICOFX100 series, long axis 2		

PRESET FULL ON

Beam angle 50%: 15° LWGN



TECHICAL DRAWINGS



CERTIFICATIONS / APPROVALS

