

PANORAMA IP65 SPOT

MUSMOV105

The PANORAMA IP SPOT is a stunning IP65 moving spotlight which is unbelievably bright. Designed to make a statement, the PANORAMA IP SPOT features 5° to 50° Zoom, CMY Colour Mixing plus Linear CTO correction and Colour Wheel.



PANORAMA IP65 SPOT

MUSMOV105

LIGHT SOURCE

Source:	420W high power white LED
CT:	7,000K
Lux:	(5°) 21,362 lux @5m
Lux:	(50°) 1173 lux @5m Full
Source life expectancy:	>20,000 h

OPTICS

Beam angle:	5°-50° Motorized linear zoom
Lens diameter:	120mm
Lens type:	HD anti-reflection lenses with achromatic coating
Focus:	Motorised with auto-focus

COLOUR SYSTEM

Colour mixing:	Linear CMY
CTC:	linear CTO correction 2700~6000K
Colour wheel:	8 dichroic filters + open

DYNAMIC EFFECTS

Rotating gobos:	7 rotating gobos + open, interchangeable, indexing
Fixed gobos:	6 fixed gobos + open, interchangeable
Gobo size:	gobo Ø 27 mm - img vØ 21 mm - 1.1 mm
FX generator:	Prisms overlap for spectacular aerial effects
Circular prism:	3facet with bi-directional rotation, indexing
Iris:	5-100% motorised linear iris
Frost:	Linear 0-100% frost filter

BODY

Pan angle:	540° - 630°
Tilt angle:	230°
Pan/Tilt resolution:	8/16 bit
Feedback:	Automatic repositioning after accidental movement
Body:	Aluminium structure with hi-resistance polycarbonate cover
Body colour:	Black

CONTROL

Protocols:	DMX512, RDM, Art-Net, W-DMX
DMX channels:	19 / 21 / 28 / 29 / 36 channel
W-DMX:	Included, wireless solution receiver
RDM:	RDM ready for fixture remote monitor and settings
Display:	LCD high resolution colour display with autoflip
Firmware upgrade:	Via menu with internal memory or via USB-DMX interface (UPBOX2) not included
Hibernation:	Power safe mode when lost DMX

ELECTRONICS

Dimmer:	Linear 0~100% mechanical dimmer
Strobe / shutter:	1~28 flash(s), mechanical
Operating temperature:	-10° ~ +45°

ELECTRICAL

Power supply:	100-240V – 50/60Hz
Power consumption (at 230V):	492W
Power consumption (at 120V):	501W

PHYSICAL

Cooling:	Forced air with low noise fan
Suspension and fixing:	Any position with quick-lock omega brackets
Signal connection:	Amphenol XLR 5p IN/OUT connectors
Data connection:	Art-Net RJ45 IN/OUT
Power connection:	Seetronic powerKon waterproof IN/OUT connectors
IP rating:	65 for outdoor events
Dimensions (WxHxD):	420x740x474mm
Weight:	38kg

