



SLIMBAR PLUS

RGBW

[Main features]

Small form factor aluminium case
In-Out connectors for fast and easy wiring
Available 100 cm and 50 cm lenght
High efficiency RGBW LEDs
Daisy chain (power and DMX)

[Optional]

- Holographic filter

Two versions:

SLIMBAR PLUS POB (on board power supply)

SLIMBAR PLUS (SLIMBAR PILOT needed)

Fixture colour finishing is grey.



ITEM	FIXTURE	100cm [KEY features]	50cm [KEY features]
LEDs	RGBW	28 RGB-NW (white 4000K)	14 RGB-NW (white 4000K)
Lumen		Red 800lm, Green 1200lm, Blue 400lm, White 1250lm	Red 400lm, Green 600lm, Blue 200lm, White 625lm
Optics	23mm lenses	PMMA 8N and ultra clear tempered glass 12°, 24°, 36°, 10°x30° - holographic filter 12°x60° to match with narrow beam	
Power		60W - 0,28A@230V	32W - 0,15A@230V
Power supply		200-240Vac; 47-63Hz; Active PFC: >0,95@230V	200-240Vac; 47-63Hz; Active PFC: >0,90@230V
Physical		1005x40x60 mm (profile dim.)	525x40x60 mm (profile dim.)
Weight		2 Kg	1 Kg
Control - Setup		Standard interface: RS-485, optocoupled input - Protocol USITT DMX512, RDM - DMX - RDM/DRS	
Connections		IN-OUT M25 fast-look connector with POWER and SIGNAL in one	

