



# RUSH MH 8 Mini Profile

The RUSH MH 8 Mini Profile is Martin Professional's smallest moving head to date with super sharp optics and an impressive output that punches above its class. High speed pan and tilt with separate colour and gobo wheels allow designers maximum flexibility from the lounge bar to the high-energy dance floor, and all within an affordable price bracket.

The MH 8 Mini Profile uses the latest 18 W white LED technology that delivers super sharp optics with over 800 lumens via a 14° beam angle. Eight varied gobos and eight vibrant colours are available, with electronic strobe/dimming, manual focus and high-speed pan and tilt. The eye-catching effects can be controlled via DMX or synchronised to a music beat via audio trig. The compact fixture weighs only 4.5kg.

## Features

- Super sharp optics
- Crisp, flat gobo projection.  
(class-leading in product category)
- Compact size and low weight
- Latest generation 18 W LED with over 800 lumens  
(class-leading in product category)
- Separate colour and gobo wheels
- Perfect for venues with low ceilings

## MARRUS013

### Physical

Length: 157 mm (6.1 in.)

Width: 237 mm (9.3 in.)

Height: 327 mm (12.9 in.)

Weight: 4.5 kg (9.9 lbs.)

### Dynamic Effects

Colour wheel: 8 colours plus open, variable and random rotation

Gobo wheel: 8 static gobos plus open, variable and random rotation

Strobe: Variable from 3 - 20 Hz, pulse effects and random strobe

Electronic dimming: 0 - 100%, four dimming curve options

Pan: 540°

Tilt: 230°

### Control and Programming

Control options: DMX, 4 stand-alone shows, master/slave

DMX channels: 10

Stand-alone trigger: Auto, music

DMX compliance: USITT DMX512/1990

Interface: Control panel with backlit LCD display

### Optics

Light source: 18 W OSRAM LE UW Q8WP LED

Minimum LED lifetime: 50 000 hours (to >70% luminous output)\*

Beam angle: 14°

Focus: Manual

*\*Figure obtained under manufacturer's test conditions*

### Construction

Colour: Black

Housing: High-impact flame-retardant thermoplastic

IP rating: IP 20

### Installation

Mounting points: Bracket for rigging clamp

Location: Dry location only, must be fastened to surface or structure

Orientation: Vertical (head down if suspended)

Minimum distance to illuminated surfaces: 200 mm (8 in.)

Minimum distance to combustible materials: 100 mm (4 in.)

Minimum clearance around fans and vents: 100 mm (4 in.)

### Connections

AC power input: IEC

DMX data in/out: 3-pin and 5-pin locking XLR

### Electrical

AC power: 100-240 V nominal, 50/60 Hz

Power supply unit: Auto-ranging electronic switch mode

Fuse: T 2.0 A

### Typical Power and Current

120 V, 60 Hz: 52 W, 0.8 A

230 V, 50 Hz: 50 W, 0.5 A

Typical half-cycle RMS inrush current: 6.4 A

Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%.

### Thermal

Cooling: Forced air (temperature-regulated, low noise)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Total heat dissipation (calculated, +/- 10%, at full intensity, full white): 180 BTU/hr.

### Approvals

EU safety: EN 60598-2-17 (EN 60598-1), EN 62471, EN 62493

EU EMC: EN 55015, EN 55032, EN 55103-2, EN 61000-3-2, EN 61000-4-2, EN 61547

US safety: UL 1573

US EMC: CFR Title 47 Part 15 Class A

Canadian safety: CSA C22.2 No. 166

Canadian EMC: ICES-003 Class A

### Installation hardware

G-clamp: P/N 91602003

Half-coupler clamp: P/N 91602005

Quick-trigger clamp: P/N 91602007

Safety cable, safe working load, 50 kg (110 lbs.): P/N 91604003

### Related Items

RUSH™ Software Uploader 1: P/N 91611399

### Ordering Information

RUSH MH 8 Mini Profile™ in cardboard box: P/N 90280110